



CONTEC®



CMS 60D

Pulse oximeter

CMS 60D

Pulse oximeter

CONTEC®

Technical specifications

- Safety
- Meet the requirement of IEC60601 series
- Type of Protection: Class II with internal electric power supply
- Degree of Protection: BF
- Dimension and Weight
- Dimension: 92(W)x82(H)x22(D)mm
- Weight: 136g(with battery)
- Operation Environment:
- Temperature: 0°C ~ +40°C
- Humidity: 15% ~ 95%
- Storage Environment:
- Temperature: -20°C ~ +60°C
- Humidity: 10% ~ 95%
- Patient Range
- Neonate, Pediatric and Adult

Features

- Routine Check Mode and Continuous Monitoring Mode
- Sync with PC based Software (WinXP and WinVista)
- Display: 1.8" Color TFT
- Resolution: 160x96
- Display Mode: Display Direction adjustable
- Indicator: Power indicator, Alarm sound, Pulse tone
- Interface: Socket for connecting SPO2 sensors and Socket for communication cables
- Power Supply: 2 AA Size Batteries DC 3V, <60MA
- Record: Data can be recorded up to 24 hours
- Alarm: Adjustable High and Low limits.

Pulse Rate

- Measurement Range: 25 ~ 250 bpm
- Resolution: 1bpm
- Accuracy: ±3 bpm (non-motion)
- Alarm Range: 25 ~ 250 bpm
- Refreshing Rate: 1s



Илан Медицинска Апаратура ООД

гр. Варна, ул. Кирил Шиваров 9 Б

тел. **0700 17373**

факс 052 612258

e-mail: office@ilan.bg

www.ilan.bg